

## **ECOVAC 200 - Liquid Filtration and Recycling Sump Cleaner**

**Mobile sump cleaning and filtering unit with 50 gallon tank capacity which will simultaneously pick-up, filter and return cleaned coolant in one continuous operation.**



|                            |                                                           |
|----------------------------|-----------------------------------------------------------|
| Suction Power:             | 110 Volts, 60 HZ, single phase, 17 Amps, max input 2.5 Hp |
| Suction Performance (air): | 80 SCFM                                                   |
| Suction Lift (water):      | 12 foot (maximum)                                         |
| Suction Rate:              | 60 GPM                                                    |

**Pump Discharge Unit:** 1/2 Hp induction motor driven open impeller centrifugal pump, protected by a large in-tank filter. The oil resistant discharge hose (10 feet x 1 inch) is fitted with a trigger actuated nozzle. Discharge rate is 20 gpm (water) @ 100 psi.

**Controls:** Splash proof On/Off Switch for suction and discharge, incorporating float actuated electrical shut-off.

**Filter Basket:** 10 Gallon capacity with 200 micron replacement nylon filter bag and 10 micron disposable bag (Other filter bags sizes are available)

**Construction:** Heavy duty mild steel tank mounted on 5 inch casters – 2 swivel and 2 fixed – for easy mobility. Includes 9" cleaning access port.

**Dimensions (L x W x H)** 48" x 27" x 48"

**Weight:** 330 pounds (Empty)

**Electrical Requirement:** 110 volts, 60 Hz, 20 Amp circuit, Single Phase